



RAE Systems, Inc.
1339 Moffett Park Dr.
Sunnyvale, CA 94089 USA

Telephone 408-752-0723
Tube Orders 1-888-723-8823
Web www.raesystems.com

Gas Detection Tube Data Sheet

Hydrogen Chloride HCl No.10-108-10

	Extended Range	Standard Range	Extended Range
Range (ppmv)	0.5 - 10	1 - 20	2 - 40
No. of Pump Strokes	2	1	0.5
Sample Volume (mL)	200	100	50
Sample Time (min)	2 x 1	1	0.5
Correction Factor	0.5	1	2

Precision (Relative Standard Deviation)*: $\leq \pm 20\%$

Linearity with No. of Pump Strokes: $r^2 = 0.999$

Humidity: Calibrated at 50% RH and 23 °C (73 °F).


% Relative Humidity	< 5%	30%	50%	70%	90%
Correction Factor @ 10 ppmv	0.7	0.8	1.0	1.1	2.7

Temperature Range: No effect between 0 - 40°C (32 - 104°F) at <5% RH.

Storage Life: 2 years in darkness at 5 - 25°C (40 - 77°F). Refrigeration preferred.

Color Change: Yellow → Pink

Reaction Principle: Pretube reduces humidity



<u>Cross-sensitivity:</u> Substance	Concentration (ppmv)	Apparent Reading*
CO	15,000	0
CO ₂	8,000	0
H ₂ S	800	0
SO ₂	200	0
NO	100	0
NO ₂	200	20
NH ₃	100	0 [^]
HF	25	15
Cl ₂	10	>20
CH ₄	25,000	0
Hexane	2400	0
Toluene	400	0

*Data based on RAE pumps and tubes used in standard range.

[^]Interferes in mixtures

Other Possible Interferences: Other acid vapors; amines and other bases.

Caution: Dispose of spent or expired tubes according to local regulations.
Possibly hazardous materials are given under the section Reaction Principle.